

DRILLING METHOD		DATUM		GRID REFERENCE		Nº	
Shell and Auger		Top of Standpipe 70.32 m OD		TL 2633 1106		764/BH3	
MACHINE				SITE			
Pilson Wayfarer				Cole Green and Holwell Court			
CONTRACTOR			LOGGED BY				
Wimpey			TL				
CONSTRUCTION	Backfill	WATER	DEPTH	REDUCED	DESCRIPTION OF STRATA		DEPTH
	Depth Fill						
	0.5 Cement		0.45	69.87	TOPSOIL		
					FIRM TO HARD LIGHT BROWN AND GREY CLAY WITH SOME CHALK AND FLINTS		
	2.5 Bentlyte Cement						
		RWL ▽	2.3	68.02			
	3.5 Bentlyte Pellets						
					COARSE/MEDIUM BROWN SAND		
		First Entry	4.2	66.12			
	6.0 Piezometer						
	6.5		6.5	63.82			
					HARD DARK GREY CLAY WITH CHALK AND FLINT PEBBLES		
	Bentlyte Pellets						
	Bentlyte Cement						
KEY				REMARKS			
Vertical Scale 1:50 2 centimetres equal 1 metre							
ASPINWALL & COMPANY				CLIENT Redland Aggregates Ltd			

DRILLING METHOD		DATUM		GRID REFERENCE		Nº	
Shell and Auger		Top of Standpipe 70.32 m OD		TL 2633 1106		764/BH3	
MACHINE				SITE			
Pilcon Wayfarer				Cole Green and Holwell Court			
CONTRACTOR			LOGGED BY				
Wimpey			TL				
CONSTRUCTION	Backfill	WATER	DEPTH	LOGGED	DESCRIPTION OF STRATA	DEPTH	LOG
	Depth Fill						
			10.3	60.02	HARD DARK GREY CLAY		
			10.5	59.82	HARD BROWN/GREY CLAY		
					BROWN CLAYEY SAND		
				59.22			
					COARSE/MEDIUM/FINE SAND AND GRAVEL		
			15.6	54.72			
					COARSE/MEDIUM/FINE SAND AND GRAVEL WITH CHALK		
			18.6	51.72			
			19.0	51.32	CHALK		
	19.0						
KEY				REMARKS			
Vertical Scale 1:50 2 centimetres equal 1 metre							
ASPINWALL & COMPANY				CLIENT Redland Aggregates Ltd			