


| DRILLING METHOD | | DATUM | | GRID REFERENCE | | Nº | |
|--|------------|--------------------------------|-----------|----------------------------------|---|---------|-------|
| Shell and Auger | | Top of Standpipe 83.55 m OD | | TL 2654 1146 | | 764/BH4 | |
| MACHINE | | | | SITE | | | |
| Pilcon Wayfarer | | | | Cole Green and Holwell Court | | | |
| CONTRACTOR | | | LOGGED BY | | | | |
| Wimpey | | | TL | | | | |
| CONSTRUCTION | Backfill | WATER | DEPTH | DEPTH | DESCRIPTION OF STRATA | | DEPTH |
| | Depth Fill | | | | | | LOW |
| | 0.5 | Cement | 0.3 | 83.25 | LIGHT BROWN CLAY FILL | | |
| | | | 1.0 | 82.55 | CLAY FILL AND REFUSE | | |
| | | | 1.2 | 82.35 | REFUSE | | |
| | | Bento-nite Cement | | | SOFT TO STIFF BROWN/GREY CLAY FILL WITH CHALK FRAGMENTS | | |
| | | | 7.5 | 76.15 | | | |
| | | | | | REFUSE (PLASTIC, PAPER, GLASS, GLASS, BRICK ETC) WITH CLAY/BRICK FILL TOWARDS BASE | | |
| | | | 9.9 | 73.65 | | | |
| KEY | | | | REMARKS | | | |
| Vertical Scale 1:50 2 centimetres equal 1 metre | | | | | | | |
| ASPINWALL & COMPANY | | | | CLIENT Redland Agrocoates Ltd | | | |

| DRILLING METHOD | | DATUM | | GRID REFERENCE | | N9 | |
|---|-------------------|--------------------------------|-----------|----------------------------------|--|----------------|-----|
| Shell and Auger | | Top of Standpipe 83.55 m OD | | TL 2654 1146 | | 764/BH4 (cont) | |
| MACHINE | | | | SITE | | | |
| Pilcon Wayfarer | | | | Cole Green and Holwell Court | | | |
| CONTRACTOR | | | LOGGED BY | | | | |
| Wimpey | | | TL | | | | |
| CONSTRUCTION | Backfill | WATER | DEPTH | DEPTH | DESCRIPTION OF STRATA | | LOG |
| | Depth Fill | | | | | | |
| | Bentonite Cement | | | | HARD BROWN/GREY CLAY WITH CHALK FRAGMENTS | | |
| 11.5 | | | | | | | |
| | Bentonite Pellets | | | | | | |
| | | RWL ▽ | 12.8 | 70.75 | | | |
| 14.0 | | First Entry | 14.0 | 69.55 | | | |
| | Sand | | | | MEDIUM/FINE BROWN/GREY SAND | | |
|  | Piezometer | | | | | | |
| 16.0 | | | | | | | |
| 16.5 | | | | | | | |
| | Bentonite Pellets | | | | BROWN SANDY FIRM CLAY GRADING INTO SOFT GREY SILTY CLAY | | |
| | | | 17.1 | 66.45 | | | |
| 18.0 | | | 17.9 | 65.65 | | | |
| | Bentonite Cement | | | | HARD DARK GREY CLAY WITH CHALK FRAGMENTS | | |
| | | | | | | | |
| KEY | | | | REMARKS | | | |
| Vertical Scale 1:50 2 centimetres equal 1 metre | | | | | | | |
| ASPINWALL & COMPANY | | | | CLIENT Redland Aggregates Ltd | | | |

| | | | | | | | |
|---|--------------------------|---|-----------------|--------------------------------------|---|----------------------|-------|
| DRILLING METHOD Shell and Auger | | DATUM Top of Standpipe 83.55 m OD | | GRID REFERENCE TL 2654 1146 | | Nº 764/BH4 (cont) | |
| MACHINE Pilcon Wayfarer | | | | SITE Cole Green and Holwell Court | | | |
| CONTRACTOR Wimpey | | | LOGGED BY TL | | | | |
| CONSTRUCTION | Backfill Depth Fill | WATER | DEPTH | BOREHOLE | DESCRIPTION OF STRATA | | DEPTH |
| | | | | | HARD DARK GREY CLAY WITH CHALK FRAGMENTS | | |
| | Bento- nite Cement | | 22.2 | 61.35 | | | |
| | | | 22.4 | 61.15 | BROWN SANDY CLAY WITH CHALK AND FLINTS | | |
| | | | | | SAND AND GRAVEL NO FURTHER PROGRESS POSSIBLE BASE OF BOREHOLE AT 22.4 m BGL | | |
| KEY Vertical Scale 1:50 2 centimetres equal 1 metre | | | | | REMARKS | | |
| ASPINWALL & COMPANY | | | | | CLIENT Redland Aggregates Ltd | | |