



Direct Drilling

BDA accredited

160 Invicta Road
Sheerness
Kent ME12 2AG

Tel / Fax : (01795) 664283
Tel : (01795) 666221
Mobile : (0831) 239668

LANDFILL
SOAKAWAYS
SITE INVESTIGATION

Depth		Strata Description	Penetration Testing and Samples									
G/L			Type	From	To	75	150	225	300	375	450	Blows
		FIRM MOTTLED BROWN CLAY, WITH SCATTERED GRAVELS, FINE BRICK FRAGMENTS AND CHALK STONES.										
1.90		WASTE, WOOD, BRICK, CONCRETE AND METAL, IN A BLACK ORGANIC CLAY MATRIX.										
9.70		SOFT TO FIRM, GREENISH-BROWN SANDY CLAY, WITH FINE CHALK STONES										
13.00		FINE TO MED GREEN SAND.										

DAY WORKS.

FILLED BOWSER FOR DRILLING = 1/2 HR.

CLEARED SPILLS TO SKIP VIA DUMPER = 1/2 HR.

COLLECTED SHINGLE FROM RADDLET AND INSTALLATION EQUIPMENT FROM YARD = 2 HRS.

Remarks INSTALLED 12.30 x 100mm LINER, DETAILS ON SEPARATE SHEET

Driller M.T. Claxton

Water Levels					
Depth	Casing	Time			
Morning					
Evening					
Other					
Depth at end of day					
Diameter (mm)	Borehole	Casing			
200	13.00	10.00			
Hard Strata / Chiselling					
From (M)	To (M)	From (Hrs)	To (Hrs)		
Total number of samples					
SPT	B	U100	D	H ² O	P

H ² O	Strike 1	Strike 2	Strike 3	
Depth	5.70	13.00		
Depth 5 mins				
Depth 10 mins				
Depth 15 mins				
Depth 20 mins				
Casing				
Cut off at				
Move	Drill	Stand	Break	Work
1	13.00			3 HRS
Site COLE GREEN				
Job No.		B / H No. V13		
Day FRIDAY		Date 22-8-97		