



Direct Drilling

BDA accredited

160 Invicta Road
Sheerness
Kent ME12 2AG

LANDFILL
SOAKAWAYS
SITE INVESTIGATION

Tel / Fax : (01795) 664283
Tel : (01795) 666221
Mobile : (0831) 239668

Depth		Strata Description	Penetration Testing and Samples							
Type	From	To	75	150	225	300	375	450	Blows	
G/L		FIRM BROWN SANDY CLAY WITH SCATTERED GRAVELS.								
1.00		WASTE, WOOD, PLASTIC, BRICK AND CONCRETE, IN A FIRM BLACK ORGANIC CLAY MATRIX.								
9.50		REDDISH-BROWN MED TO COARSE SAND WITH MED SIZED GRAVELS.								
11.70		GREENISH-BROWN FINE TO MED SAND.								
13.50		REDDISH-BROWN FINE TO MED SAND.								
14.80		STIFF, DARK GRAY SILTY CLAY WITH FINE CHALK STONES AND CHALK FRAGMENTS.								
DRILLED TO 15.30										
Remarks			INSTALLED 15.60 x 100mm LINER, DETAILS ON SEPARATE SHEET.					Driller		
								<i>M. J. Claxton</i>		
Water Levels			H ² O	Strike 1	Strike 2	Strike 3				
Depth	Casing	Time	Depth	9.00						
Morning			Depth 5 mins							
Evening			Depth 10 mins							
Other			Depth 15 mins							
Depth at end of day			Depth 20 mins							
Diameter (mm)	Borehole	Casing	Casing							
200	15.30	15.00	Cut off at							
Hard Strata / Chiselling				Move	Drill	Stand	Break	Work		
From (M)	To (M)	From (Hrs)	To (Hrs)	1	15.30			3 HR.		
				Site						
				COLE GREEN.						
				Job No.			B / H No.			
							V15			
				Day			Date			
				TUES / WEDNESDAY			19/20 - 8 - 97			